

24Mt IMO1 Rated Bitutainer™  
 Model TR-T-679-UL  
 (For Thermal Fluid Heating)



UL 142 Certified for Storage and Fully Intermodal for Transportation of Heavy Fuel Oil (HFO), Bitumen and Light Fuel Oils

**Fully IMDG Compliant with ADR/RID, US DOT/TC, UL 142**

- Nominal Capacity 24,000 Litres
- ISO 1496 Part 3 - Type 75 “Tank Containers”
- Inner Vessel Pressure Tested to 4.0 bar
- High Performance factory fitted heating tubes suitable for heating with Thermal Fluid
- Baffled design allows Partial Payloads to be carried
- High Value Factory Installed Insulation and Pressed Corten Steel Outer Skin
- Fully Framed with Corner Twist Locks and Damage Reinforcement Plates
- UN Coded T3 (IMO1 rated) Tank Container with Lloyds Approval
- Fully Bunded and fitted with High Level Connections and Internal Dropper Pipes



**Multiple Interface Options for Product, Heating and Level Control**

**Ratings:**  
 Max GW 30,480 Kgs  
 Payload 23,630 Kgs  
 Tare Wt. <6,850 Kgs

**Measures:**  
 Length 6,058 mm (20')  
 Width 2,438 mm (8')  
 Height 2,591 mm (8'6")